


## DOWNLIGHT LIDER Z 930 21W 60° WHITE PREMIUM COLOR ON/OFF

Article number: N202-K0003-PC930-HA-G60-ZA02\_550-S1-###





COB

3000 [K] PREMIUM COLOR Light colour

CRI

90 Led chip flux 2396 [lm] Luminous flux 2156 [lm] System power 21 [W] Luminaire Efficiency 103 [lm/W] Beam angle 60°

Controller ON/OFF MacAdam 3 SDCM

## LUMINAIRE

Weight 1,17 [kg] Protection rating IP, IK, class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

## **Downlight LED**

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00





www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska