


DOWNLIGHT LIDER Z 940 14W 60° WHITE PREMIUM WHITE ON/OFF

Article number: N202-K0003-PW940-HA-G60-ZA01_350-S1-###





COB

4000 [K] PREMIUM WHITE Light colour

CRI 90

Led chip flux

1887 [lm] Luminous flux 1698 [lm] System power 14 [W] Luminaire Efficiency 121 [lm/W]

60° Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

Beam angle

Weight 1,17 [kg] Protection rating IP, IK, class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska