

DOWNLIGHT LIDER Z 827 31W 23° WHITE | ON/OFF

Article number: N202-K0003-RF827-H5-G23-ZA03_800-S1-###



COB

80

2700 [K] |

4311 [lm]

3879 [lm]


125 [lm/W]

ON/OFF

3 SDCM

31 [W]

23°



| Dov | ght | LED |
|-----|-----|-----|
| | | |

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

| U | M | IN | Α | IR | E |
|---|---|----|---|----|---|

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| JMINAIRE | | | | | | |
|------------------|--|--|--|--|--|--|
| 1,17 [kg] | | | | | | |
| IP 20, IK 1, | | | | | | |
| WHITE | | | | | | |
| Plastic | | | | | | |
| 220-240V 50-60Hz | | | | | | |
| | | | | | | |

ic 240V 50-60Hz

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

Generated: 29.06.2024