

DOWNLIGHT LIDER Z 830 21W 15° WHITE | ON/OFF

Article number: N202-K0003-RF830-H5-G15-ZA02_550-S1-###



СОВ

80 2994 [lm]

3000 [K] |

2694 [lm]


128 [lm/W]

ON/OFF

3 SDCM

21 [W]

15°



D			-
Down	iign	τLE	Ð

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	111	Л	Ν	ΔI	R	F.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
1,17 [kg]				
IP 20, IK 1,				
WHITE				
Plastic				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024