

DOWNLIGHT LIDER Z 840 27W 60° WHITE | ON/OFF

Article number: N202-K0003-RF840-H5-G60-ZA02_700-S1-###



COB

80 3974 [lm]

4000 [K] |

3576 [lm]


132 [lm/W]

ON/OFF

3 SDCM

27 [W]

60°



Downli	abt	
DOWIII	ynu	LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	110	ЛТ	NI.	ΛI	P	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE					
1,17 [kg]					
IP 20, IK 1,					
WHITE					
Plastic					
220-240V 50-60Hz					

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 26.06.2024