

DOWNLIGHT LIDER Z 850 23W 15° WHITE | ON/OFF

Article number: N202-K0003-RF850-H5-G15-ZA02_600-S1-###



СОВ

80 3475 [lm]

5000 [K] |

3127 [lm]


136 [lm/W]

ON/OFF

3 SDCM

23 [W]

15°



Downlig	ght LED
---------	---------

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

н	ш	M	IN	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
1,17 [kg]				
IP 20, IK 1,				
WHITE				
Plastic				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 16.06.2024