


DOWNLIGHT LIDER Z 927 19W 45° WHITE | ON/OFF

Article number: N202-K0003-RF927-H5-G45-ZA01_500-S1-###



| | |
|----------------------|------------|
| LED | COB |
| Light colour | 2700 [K] |
| CRI | 80 |
| Led chip flux | 2222 [lm] |
| Luminous flux | 1999 [lm] |
| System power | 19 [W] |
| Luminaire Efficiency | 105 [lm/W] |
| Beam angle | 45° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

LUMINAIRE

| | |
|-----------------------------------|------------------|
| Weight | 1,17 [kg] |
| Protection rating IP , IK , class | IP 20, IK 1, |
| Luminaire colour | WHITE |
| Cover | Plastic |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska