


DOWNLIGHT LIDER Z 825 14W 23° WHITE BREAD ON/OFF

Article number: N202-K0003-VF825-H5-G23-ZA01_350-S1-###





LED COB

Light colour 2500 [K] BREAD

CRI 8

 Led chip flux
 1674 [lm]

 Luminous flux
 1506 [lm]

 System power
 14 [W]

 Luminaire Efficiency
 108 [lm/W]

Beam angle23°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

Weight 1,17 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska