

DOWNLIGHT LIDER M 940 14W 23° GREY HI EFFICIENT ON/OFF

Article number: N203-K0001-BB940-H5-M23-ZC01_350-S2-###



LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	90
Led chip flux	2260 [lm]
Luminous flux	2034 [lm]
System power	14 [W]
Luminaire Efficiency	145 [lm/W]
Beam angle	23°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 16.05.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska