

DOWNLIGHT LIDER M 940 21W 38° GREY HI EFFICIENT ON/OFF

Article number: N203-K0001-BB940-H5-M38-ZC02_550-S2-###



LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI Led chip flux	90
Luminous flux	3492 [lm]
System power	3142 [lm] 21 [W]
Luminaire Efficiency Beam angle	150 [lm/W]
Controller	38°
MacAdam	ON/OFF 3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska