

DOWNLIGHT LIDER M 957 10W 15° GREY SPECIAL ON/OFF

Article number: N203-K0001-CC957-H5-M15-ZC01_250-S2-###



COB 5700 [K] SPECIAL Light colour CRI Led chip flux 1318 [lm] Luminous flux 1186 [lm] System power 10 [W] Luminaire Efficiency 119 [lm/W] Beam angle 15° Controller ON/OFF

LUMINAIRE

MacAdam

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.05.2024



+48 32 388 80 00



3 SDCM

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska