

DOWNLIGHT LIDER M 957 23W 45° GREY SPECIAL ON/OFF

Article number: N203-K0001-CC957-H5-M45-ZC02_600-S2-###



 LED
 COB

 Light colour
 5700 [K] SPECIAL

 CRI
 90

 Led chip flux
 3023 [Im]

 Luminous flux
 2720 [Im]

 System power
 23 [W]

 Luminaire Efficiency
 118 [Im/W]

 Beam angle
 45°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska