

DOWNLIGHT LIDER M 930 20W 60° GREY PREMIUM WHITE ON/OFF

Article number: N203-K0001-HE930-HA-M60-ZC01_500-S2-###



LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI 90

Led chip flux 2880 [lm]

Luminous flux 2592 [lm]

System power

20 [W]

Luminaire Efficiency

Beam angle 130 [lm/W]
Controller 60°

MacAdam ON/OFF

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 17.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska