

## DOWNLIGHT LIDER M 930 25W 15° GREY CRI97 ON/OFF

Article number: N203-K0001-HI930-H5-M15-ZC02\_650-S2-###



|                      |                |
|----------------------|----------------|
| LED                  | COB            |
| Light colour         | 3000 [K] CRI97 |
| CRI                  | 90             |
| Led chip flux        | 2797 [lm]      |
| Luminous flux        | 2517 [lm]      |
| System power         | 25 [W]         |
| Luminaire Efficiency | 101 [lm/W]     |
| Beam angle           | 15°            |
| Controller           | ON/OFF         |
| MacAdam              | 3 SDCM         |

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 0,61 [kg]        |
| Protection rating IP , IK , class | IP 20, IK 1,     |
| Luminaire colour                  | GREY             |
| Cover                             | Plastic          |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska