


DOWNLIGHT LIDER M 930 19W 38° GREY CRI97 ON/OFF

Article number: N203-K0001-HI930-H5-M38-ZC01_500-S2-###





LED	COB
P. D. T.	0000

3000 [K] CRI97 Light colour

CRI

2199 [lm] Led chip flux Luminous flux 1979 [lm] System power 19 [W] Luminaire Efficiency 104 [lm/W] Beam angle 38° Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg] Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska