

DOWNLIGHT LIDER M 930 21W 45° GREY PREMIUM COLOR ON/OFF

Article number: N203-K0001-PC930-HA-M45-ZC02_550-S2-###



LED COB

Light colour 3000 [K] PREMIUM COLOR

CRI

90 Led chip flux

2396 [lm]

Luminous flux

System power

Luminaire Efficiency

2396 [lm]

2156 [lm]

21 [W]

103 [lm/W] Beam angle

Controller 45°

MacAdam ON/OFF

LUMINAIRE

 Weight
 0,61 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 GREY

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska