

DOWNLIGHT

DOWNLIGHT LIDER M 940 21W 38° GREY PREMIUM WHITE ON/OFF

Article number: N203-K0001-PW940-HA-M38-ZC02_550-S2-###



4000 [K] PREMIUM WHITE

COB

90

2912 [lm]

2620 [lm]


125 [lm/W]

ON/OFF

3 SDCM

21 [W]

38°



Down	lia	ht	
DOWIN	ny	ш.	ᄕ

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024