

DOWNLIGHT LIDER M 940 25W 38° GREY PREMIUM WHITE ON/OFF

25 [W]

Article number: N203-K0001-PW940-HA-M38-ZC02_650-S2-###



LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

Led chip flux

3398 [lm]
Luminous flux

System power

3058 [lm]

Luminaire Efficiency
122 [Im/W]

Beam angle 38° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska