

DOWNLIGHT

DOWNLIGHT LIDER M 830 25W 15° GREY | ON/OFF

Article number: N203-K0001-RF830-H5-M15-ZC02_650-S2-###



LED	COB	Downl
Light colour	3000 [K]	LED do include on enq is 27W
CRI	80	
Led chip flux	3538 [lm]	
Luminous flux	3184 [lm]	
System power	25 [W]	
Luminaire Efficiency	127 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,61 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note

GREY

Plastic

220-240V 50-60Hz

Downlight LED

ED downlight for drop ceiling istallation. Aluminium housing. Plastic cover ncluded. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power s 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024