

DOWNLIGHT

DOWNLIGHT LIDER M 835 21W 23° GREY | ON/OFF

Article number: N203-K0001-RF835-H5-M23-ZC02_550-S2-###



COB

80

3500 [K] |

3061 [lm]

2754 [lm]


131 [lm/W]

ON/OFF

3 SDCM

21 [W]

23°



Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,61 [kg]
5	IP 20, IK 1,
Protection rating IP , IK , class	
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024