

DOWNLIGHT

## DOWNLIGHT LIDER M 840 14W 23° GREY | ON/OFF

Article number: N203-K0001-RF840-H5-M23-ZC01\_350-S2-###



LED	COB	Downlight LED
Light colour	4000 [K]	LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power
CRI	80	
Led chip flux	1987 [lm]	is 27W.
Luminous flux	1788 [lm]	
System power	14 [W]	
Luminaire Efficiency	128 [lm/W]	
Beam angle	23°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,61 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All data are typical values. Tolerance of measurements +/-10% System

GREY

Plastic

220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024