

DOWNLIGHT

DOWNLIGHT LIDER M 850 10W 38° GREY | ON/OFF

COB

80

5000 [K] |

1447 [lm]

1302 [lm]

130 [lm/W]

ON/OFF

3 SDCM

10 [W]

38°

Article number: N203-K0001-RF850-H5-M38-ZC01_250-S2-###



Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LU	MI	NA	IR	E

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,61 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	
Luminaire colour	GREY	
Cover	Plastic	
Operating voltage	220-240V 50-60Hz	

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska