

DOWNLIGHT LIDER M 940 14W 45° GREY | ON/OFF

Article number: N203-K0001-RF940-H5-M45-ZC01_350-S2-###



| LED | COB |
|----------------------|------------|
| Light colour | 4000 [K] |
| CRI | 90 |
| Led chip flux | 1691 [lm] |
| Luminous flux | 1521 [lm] |
| System power | 14 [W] |
| Luminaire Efficiency | 109 [lm/W] |
| Beam angle | 45° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska