

## DOWNLIGHT LIDER M 930 27W 60° BLACK HI EFFICIENT ON/OFF

Article number: N203-K0002-BB930-H5-M60-ZC01\_700-S2-###



0,61 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz



LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux Luminous flux	4378 [lm]
System power	3940 [lm]
Luminaire Efficiency	27 [W]
Beam angle	146 [lm/W] 60°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	

## Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024