

DOWNLIGHT LIDER M 935 14W 23° BLACK HI EFFICIENT ON/OFF

Article number: N203-K0002-BB935-H5-M23-ZC01_350-S2-###



0,61 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI Led chip flux Luminous flux	90 2174 [lm] 1956 [lm]
System power Luminaire Efficiency Beam angle Controller MacAdam	14 [W] 140 [Im/W] 23° ON/OFF 3 SDCM
LUMINAIRE	3 SDOW

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generaled: 17.05.2024