

DOWNLIGHT LIDER M 935 23W 60° BLACK HI EFFICIENT ON/OFF

Article number: N203-K0002-BB935-H5-M60-ZC02_600-S2-###



0,61 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI Led chip flux Luminous flux System power	90 3624 [lm] 3261 [lm]
Luminaire Efficiency Beam angle Controller MacAdam	23 [W] 142 [Im/W] 60° ON/OFF 3 SDCM
LUMINAIRE	

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024