

DOWNLIGHT LIDER M 940 27W 23° BLACK HI EFFICIENT ON/OFF

Article number: N203-K0002-BB940-H5-M23-ZC01_700-S2-###



LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	
Led chip flux	90
	4385 [lm]
Luminous flux	3946 [lm]
System power	27 [\\/]
Luminaire Efficiency	27 [W]
Beam angle	146 [lm/W]
	23°
Controller	ON/OFF
MacAdam	3 SDCM
	3 2DCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 77W

LUMINAIRE

Weight 0,61 [kg]
Protection rating IP , IK , class IP 20, IK 1,
Luminaire colour BLACK
Cover Plastic
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska