

DOWNLIGHT

DOWNLIGHT LIDER M 930 19W 38° BLACK CRI97 ON/OFF


Article number: N203-K0002-HI930-H5-M38-ZC01_500-S2-###



BLACK

Plastic

220-240V 50-60Hz



LED	COB
Light colour	3000 [K] CRI97
CRI	90
Led chip flux	2199 [lm]
Luminous flux	1979 [lm]
System power	19 [W]
Luminaire Efficiency	104 [lm/W]
Beam angle	38°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
Weight	0,61 [kg]
Protection rating IP, IK, class	IP 20, IK 1,

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024