

DOWNLIGHT

DOWNLIGHT LIDER M 827 25W 15° BLACK | ON/OFF

Article number: N203-K0002-RF827-H5-M15-ZC02_650-S2-###



IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



LED	COB
Light colour	2700 [K]
CRI	80
Led chip flux	3502 [lm]
Luminous flux	3151 [lm]
System power	25 [W]
Luminaire Efficiency	126 [lm/W]
Beam angle	15°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
Weight	0,61 [kg]

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska