

DOWNLIGHT

DOWNLIGHT LIDER M 927 25W 60° BLACK | ON/OFF

Article number: N203-K0002-RF927-H5-M60-ZC02_650-S2-###



IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



| LED | COB |
|----------------------|------------|
| Light colour | 2700 [K] |
| CRI | 80 |
| Led chip flux | 2888 [lm] |
| Luminous flux | 2599 [lm] |
| System power | 25 [W] |
| Luminaire Efficiency | 104 [lm/W] |
| Beam angle | 60° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |
| LUMINAIRE | |
| Weight | 0,61 [kg] |

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

Luminaire colour Cover

Protection rating IP , IK , class

Operating voltage

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska