


DOWNLIGHT

## DOWNLIGHT LIDER M 930 10W 38° BLACK | ON/OFF

Article number: N203-K0002-RF930-H5-M38-ZC01\_250-S2-###





	LED	COB
	Light colour	3000 [K]
	CRI	90
	Led chip flux	1152 [lm]
	Luminous flux	1036 [lm]
	System power	10 [W]
	Luminaire Efficiency	104 [lm/W]
	Beam angle	38°
	Controller	ON/OFF
	MacAdam	3 SDCM
LUMINAIRE		
	Weight	0,61 [kg]
	Protection rating IP , IK , class	IP 20, IK 1,
	Luminaire colour	BLACK

Plastic

220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024