


## DOWNLIGHT LIDER M 930 25W 45° BLACK | ON/OFF

Article number: N203-K0002-RF930-H5-M45-ZC02\_650-S2-###





LED	COB
Light colour	3000 [K]
CRI	90
Led chip flux	2997 [lm]
Luminous flux	2697 [lm]
System power	25 [W]
Luminaire Efficiency	108 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

## LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 15.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska