


DOWNLIGHT

## DOWNLIGHT LIDER M 940 19W 38° BLACK | ON/OFF

Article number: N203-K0002-RF940-H5-M38-ZC01\_500-S2-###





	LED	COB	D
	Light colour	4000 [K]	L
	CRI	90	ir o
	Led chip flux	2416 [lm]	is
	Luminous flux	2174 [lm]	
	System power	19 [W]	
	Luminaire Efficiency	114 [lm/W]	
	Beam angle	38°	
	Controller	ON/OFF	
	MacAdam	3 SDCM	
L	UMINAIRE		
	Weight	0,61 [kg]	
	Protection rating IP , IK , class	IP 20, IK 1,	
	Luminaire colour	BLACK	

Plastic

220-240V 50-60Hz

## Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024