

DOWNLIGHT LIDER M 825 10W 15° BLACK BREAD ON/OFF

COB

Article number: N203-K0002-VF825-H5-M15-ZC01_250-S2-###



 Light colour
 2500 [K] BREAD

 CRI
 80

 Led chip flux
 1195 [Im]

 Luminous flux
 1075 [Im]

 System power
 10 [W]

 Luminaire Efficiency
 108 [Im/W]

Beam angle15°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

LED

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska