


DOWNLIGHT LIDER M 825 21W 15° BLACK BREAD ON/OFF

Article number: N203-K0002-VF825-H5-M15-ZC02_550-S2-###





LED COB

Light colour 2500 [K] BREAD

CRI 80

Led chip flux 2574 [lm]

Luminous flux 2316 [lm]

System power 21 [W]

Luminaire Efficiency 110 [lm/W]

Beam angle 15°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

 Weight
 0,61 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 BLACK

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements $\pm 10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 15.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska