

DOWNLIGHT LIDER M 825 14W 23° BLACK BREAD ON/OFF

COB

Article number: N203-K0002-VF825-H5-M23-ZC01_350-S2-###



 Light colour
 2500 [K] BREAD

 CRI
 80

 Led chip flux
 1674 [Im]

 Luminous flux
 1506 [Im]

 System power
 14 [W]

 Luminaire Efficiency
 108 [Im/W]

 Beam angle
 23°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

LED

 Weight
 0,61 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 BLACK

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska