


DOWNLIGHT LIDER M 935 25W 15° WHITE HI EFFICIENT ON/OFF

Article number: N203-K0003-BB935-H5-M15-ZC02_650-S2-###





LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	
Led chip flux	90
Luminous flux	3904 [lm]
System power	3513 [lm]
	25 [W]
Luminaire Efficiency	141 [lm/W]
Beam angle	15°
Controller	
MacAdam	ON/OFF
	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 15.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska