


DOWNLIGHT LIDER M 935 10W 45° WHITE HI EFFICIENT ON/OFF

Article number: N203-K0003-BB935-H5-M45-ZC01_250-S2-###





COB 3500 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 1571 [lm] Luminous flux 1413 [lm] System power 10 [W] Luminaire Efficiency 141 [lm/W] Beam angle 45° Controller ON/OFF MacAdam 3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

 $\ensuremath{\mathsf{RAL}}$ colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 17.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska