

#### DOWNLIGHT

## DOWNLIGHT LIDER M 942 27W 23° WHITE MEAT WHITE ON/OFF

Article number: N203-K0003-CC942-H5-M23-ZC01\_700-S2-###



COB

90

2695 [lm]

2425 [lm]

90 [lm/W]


ON/OFF

3 SDCM

27 [W]

23°

4200 [K] MEAT WHITE



#### Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

#### LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024