


DOWNLIGHT LIDER M 942 27W 60° WHITE MEAT WHITE ON/OFF

Article number: N203-K0003-CC942-H5-M60-ZC01_700-S2-###









LED	COB
Light colour	4200 [K] MEAT WHITE
CRI	90
Led chip flux	
Luminous flux	2695 [lm]
Custom neurox	2425 [lm]
System power	27 [W]
Luminaire Efficiency	90 [lm/W]
Beam angle	
Controller	60°
MacAdam	ON/OFF
IviavAuaiii	3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power

LUMINAIRE

0,61 [kg] Weight Protection rating IP, IK, class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska