

## DOWNLIGHT

## DOWNLIGHT LIDER M 957 14W 38° WHITE SPECIAL ON/OFF

COB

90

1820 [lm]

1638 [lm]

117 [lm/W]

ON/OFF

3 SDCM


14 [W]

38°

5700 [K] SPECIAL

Article number: N203-K0003-CC957-H5-M38-ZC01\_350-S2-###





D	own	ligh	nt L	ED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LU	MI	NA	IR	E

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
	220-240V 50-60Hz
Operating voltage	220-240V 30-60HZ

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.05.2024