


DOWNLIGHT LIDER M 957 19W 60° WHITE SPECIAL ON/OFF

Article number: N203-K0003-CC957-H5-M60-ZC01_500-S2-###





LED COB

Light colour 5700 [K] SPECIAL

CRI 9

Led chip flux2551 [lm]Luminous flux2295 [lm]System power19 [W]Luminaire Efficiency121 [lm/W]Beam angle60°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.202



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska