

## DOWNLIGHT

# DOWNLIGHT LIDER M 930 27W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N203-K0003-HE930-HA-M45-ZC01\_700-S2-###



LED	COB
Light colour	3000 [K] PREMIUM WHITE
CRI	00
Led chip flux	90
Luminous flux	3911 [lm]
Luminous nux	3519 [lm]
System power	5. d
Luminaire Efficiency	27 [W]
Beam angle	130 [lm/W]
Deamangle	45°
Controller	
MacAdam	ON/OFF
	3 SDCM

## Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

# LUMINAIRE

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### **OPTIONS**

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024