


DOWNLIGHT LIDER M 930 21W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N203-K0003-HE930-HA-M45-ZC02_550-S2-###





ED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90 Led chip flux

3143 [lm] Luminous flux

2828 [lm]
System power
21 [W]

Luminaire Efficiency
135 [Im/W]

Beam angle 45°

Controller ON/OFF

3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska