

DOWNLIGHT

DOWNLIGHT LIDER M 930 27W 45° WHITE CRI97 ON/OFF

Article number: N203-K0003-HI930-H5-M45-ZC01_700-S2-###



LED	COB	Downl			
Light colour CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	3000 [K] CRI97 90 2990 [Im] 2691 [Im] 27 [W] 100 [Im/W] 45° ON/OFF 3 SDCM	LED do include on enq is 27W			
				LUMINAIRE	
		Weight		0,61 [kg]	
		Protection rating IP , IK , class		IP 20, IK 1,	Note

WHITE

Plastic

220-240V 50-60Hz

nlight LED

downlight for drop ceiling istallation. Aluminium housing. Plastic cover ded. Available in white, black and grey. Any RAL palette colour available quiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power *W*.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Generated: 15.05.2024