


DOWNLIGHT LIDER M 940 21W 38° WHITE PREMIUM WHITE ON/OFF

Article number: N203-K0003-PW940-HA-M38-ZC02_550-S2-###





COB

4000 [K] PREMIUM WHITE Light colour

CRI 90

Led chip flux 2912 [lm] Luminous flux 2620 [lm] System power 21 [W] Luminaire Efficiency 125 [lm/W] Beam angle

38° Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg] Protection rating IP, IK, class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska