

DOWNLIGHT LIDER M 940 14W 45° WHITE PREMIUM WHITE ON/OFF

COB

90

1887 [lm]

1698 [lm]

121 [lm/W]

ON/OFF

3 SDCM


14 [W]

45°

4000 [K] PREMIUM WHITE

Article number: N203-K0003-PW940-HA-M45-ZC01_350-S2-###





Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

0,61 [kg]
IP 20, IK 1,
WHITE
Plastic
220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

