


DOWNLIGHT LIDER M 830 10W 15° WHITE | ON/OFF

Article number: N203-K0003-RF830-H5-M15-ZC01_250-S2-###



3000 [K] |



СОВ

CRI 8

 Led chip flux
 1361 [lm]

 Luminous flux
 1224 [lm]

 System power
 10 [W]

Luminaire Efficiency 122 [lm/W]

Beam angle 15°

Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Light colour

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska