


## DOWNLIGHT LIDER M 830 10W 38° WHITE | ON/OFF

Article number: N203-K0003-RF830-H5-M38-ZC01\_250-S2-###



LED	COB
Light colour	3000 [K]
CRI	80
Led chip flux	1361 [lm]
Luminous flux	1224 [lm]
System power	10 [W]
Luminaire Efficiency	122 [lm/W]
Beam angle	38°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

### LUMINAIRE

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska