

DOWNLIGHT LIDER M 840 23W 38° WHITE | ON/OFF

COB

80

4000 [K] |

3407 [lm]

3066 [lm]

133 [lm/W]

ON/OFF

3 SDCM

23 [W]

38°

Article number: N203-K0003-RF840-H5-M38-ZC02_600-S2-###



Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| Weight | 0,61 [kg] |
|-----------------------------------|------------------|
| Protection rating IP , IK , class | IP 20, IK 1, |
| Luminaire colour | WHITE |
| Cover | Plastic |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska